GP Batteries

Product Portfolio

PowerBank + Rechargeable Batteries

STAYING AHEAD WITH GP Batteries

As an expert principally engaged in the development, manufacturing and marketing of rechargeable and primary battery products, GP Batteries is one of the world's leading battery manufacturers and the no.1 in Asia outside of Japan.

To keep up with the fast-moving hi-tech world and the rocketing popularity of power hungry electronic devices, GP Batteries has a comprehensive range of chargers and the best-in-class Nickel Metal Hydride rechargeable batteries to meet users' needs.

Each of these high performance, feature-packed GP PowerBank is ready to stun tech fans with an exciting blend of stylish design and outstanding capabilities. Cost-efficient and environmentally friendly, there's no doubt they are the indispensable for every household.

Known for its superior products and quality reliability, GP Batteries is the major back-up provider for leading electronic manufacturers. It has marketing and trading offices all over Asia, North and South America, Europe and Middle East

Keeping to the fore of progress in the almost daily changing innovative world of high-tech, GP Batteries is the consumers' No.1 battery manufacturer for portable electronics and the retailers' guarantee of product reliability.

INDEX

PREMIUM SERIES P.4

FAST SERIES P.8

MID-RANGE SERIES P.11

STANDARD SERIES P.17

SPECIALTY SERIES P.23

NiMH RECHARGEABLE BATTERIES P.28

PB80

V800C

PowerBank

- 15 mins to charge up 2 pcs NiMH batteries
- Digital clock
- Easy check 3-color LED icons to show charging status
- Safe standby switch to initiate charging process
- Auto cut-off safety control by voltage, temperature and time to prevent overcharging
- Individual charging channels, can charge 1-4 pcs of NiMH AA or AAA in any combinations
- GP Patented Smart Recharge Technology
- Primary & bad battery detection
- AC100-240V worldwide use

4 x 2700 series AA

4 x 2500 series AA

PB60

V600D PowerBank

- 1 hour to charge up 2 pcs NiMH batteries
- Easy check LCD display to show charging status
- Safe standby switch to initiate charging process
- Auto cut-off safety control by voltage, temperature and time to prevent overcharging
- Individual charging channels, can charge 1-4 pcs of NiMH AA or AAA in any combinations
- GP Patented Smart Recharge Technology
- Primary & bad battery detection
- AC100-240V worldwide use

4 x 2700 series AA

4 x 2500 series AA

PB65

H650C PowerBank

- 1 hour to charge up 4 pcs NiMH batteries
- Digital clock
- Easy check 3-color LED icons to show charging status
- Auto cut-off safety control by voltage, temperature and time to prevent overcharging
- Individual charging channels, can charge 1-4 pcs of NiMH AA or AAA in any combinations
- GP Patented Smart Recharge Technology
- Primary & bad battery detection
- AC100-240V worldwide use
- DC12V car charging function (optional)

4 x 2700 series AA

4 x 2500 series AA

PowerBank H500

- 2 hours to charge up 2 pcs NiMH batteries
- Battery ejector to easily unload batteries
- Easy check 3-color LED icons to show charging status
- Auto cut-off safety control by voltage, temperature and time to prevent overcharging
- Individual charging channels, can charge 1-4 pcs of NiMH AA or AAA in any combinations
- Primary & bad battery detection
- AC100-240V for EU / UK version, AC 100-120V for US version
- DC12V car charging function (optional)

PB50

4 x 2700 series AA

4 x 2500 series AA

15 MINS
CHARGING TIME

PB15

EXPRESS

PowerBank

- 15 mins to charge up 4 pcs NiMH batteries
- LED indicator
- Auto cut-off safety control by voltage, temperature and time to prevent overcharging
- Individual charging channels, can charge 1-4 pcs of NiMH AA or AAA in any combinations
- GP Patented Smart Recharge Technology
- Primary & bad battery detection
- AC100-240V worldwide use
- DC14V car charging function (optional)

4 x 2700 series AA

4 x 2500 series AA

U-SMART

PowerBank

- 30 mins to charge up 4 pcs NiMH batteries
- 4 dual color LED indicators
- Auto cut-off safety control by voltage, temperature and time to prevent overcharging
- Individual charging channels, can charge 1-4 pcs NiMH AA or AAA in any combinations
- GP Patented Smart Recharge Technology
- Primary & bad battery detection
- AC100-240V worldwide use
- DC12V car charging function (optional)

PB13

4 x 2700 series AA

4 x 2500 series AA

SMART 2
PowerBank

- 1 hour to charge up 4 pcs NiMH
- 4 LED indicators
- Auto cut-off safety control by voltage, temperature and time to prevent overcharging
- Individual charging channels, can charge 1-4 pcs NiMH AA or AAA in any combinations
- GP Patented Smart Recharge Technology
- Primary & bad battery detection
- AC100-240V worldwide use
- DC12V car charging function (optional)

PB14

4 x 2700 series AA

4 x 2500 series AA

M520 PowerBank

- 2 hours to charge up 2 pcs NiMH batteries
- Dual color LED indicator
- Auto cut-off safety control by voltage, temperature and time to prevent overcharging
- Two charging channels, can charge 2 or 4 pcs NiMH AA or 2 pcs NiMH AAA
- Primary & bad battery detection
- AC100-240V worldwide use
- DC12V car charging function (optional)

PB520

4 x 2500 series AA

4 x 2300 series AA

M530
PowerBank

PB530

- 2 hours to charge up 1 pc NiMH battery through a USB port on computer
- Dual color LED indicator
- Auto cut-off safety control by voltage, temperature and time to prevent overcharging
- Foldable USB plug
- Powered by computer
- Individual charging channels, can charge 1or 2 pcs NiMH AA, AAA or AAAA
- Primary & bad battery detection

4 x 2500 series AA

4 x 2300 series AA

PB540

M540 PowerBank

- 3 hours to charge up 1 to 4 pcs NiMH AA or AAA batteries
- Ultra compact and lightweight
- Detachable adaptor plugs (US, EU & UK) for traveller convenience
- Dual color LED indicator
- Auto cut-off safety control by voltage, temperature and time to prevent overcharging
- Individual charging channels, can charge 1-4 pcs NiMH AA or AAA in any combinations
- Primary battery & bad battery detection
- AC100-240V worldwide use

4 x 2500 series AA

4 x 2300 series AA

PB25

MINI QUICK PowerBank

- 5 hours to charge up 2 pcs NiMH batteries
- Slim and compact design
- Dual color LED indicator
- Auto cut-off safety control by temperature and time to prevent overcharging
- Individual charging channels, can charge 1 or 2 pcs NiMH AA or AAA
- Primary & bad battery detection
- AC100-240V worldwide use

2 x 2500 series AA

2 x 2300 series AA

PB27

QUICK 3 PowerBank

- 8 hours to charge up 4 pcs NiMH batteries
- USB output port for charging electronic devices
- Ultra slim design
- Dual color LED indicator
- Auto cut-off safety control by temperature and time to prevent overcharging
- Two charging channels, can charge 2 or 4 pcs NiMH AA or 2 pcs NiMH AAA
- Primary & bad battery detection
- AC100-240V worldwide use

USB Power Port

4 x 2500 series AA

4 x 2300 series AA

MEGA PowerBank

- 6 hours to charge up 8 pcs NiMH batteries
- Slim and unique design
- Two dual color LED indicators
- Auto cut-off safety control by temperature and time to prevent overcharging
- Two charging channels, can charge 4 or 8 pcs NiMH AA or AAA

6 HRS CHARGING TIME

PB22

4 x 2100 series AA

PB11

NITE-LITE PowerBank

- Always plug-in design for instant energy
- Built-in night light function
- Two charging channels, can charge 2 or 4 pcs NiMH AA or AAA
- Additional charging slots for 1 or 2 pcs NiMH 9V batteries
- Two LED indicators

4 x 2100 series AA

4 x 1800mAh AA

KB01

PowerBank

- Always plug-in design for instant energy
- Two charging channels, can charge 2 or 4 pcs NiMH AA or AAA
- Two LED indicators

4 x 2100 series AA

4 x 1800mAh AA

MINI PowerBank

- Always plug-in design for instant energy
- Two charging channels, can charge 1 or 2 pcs NiMH AA or AAA
- Two LED indicators

KB02

2 x 2100 series AA

2 x 1800mAh AA

PB350

S350
PowerBank

- Always plug-in design for instant energy
- Unique design
- Two charging channels, can charge 2 or 4 pcs NiMH AA or AAA
- Two LED indicators

4 x 2100 series AA

4 x 1800mAh AA

S360 PowerBank

- Always plug-in design for instant energy
- Unique design
- Two charging channels, can charge 1-2 pcs NiMH AA or AAA
- Two LED indicators

PB360

2 x 2100 series AA

2 x 1800mAh AA

PB19

UNIVERSAL PowerBank

- Universal for household use
- Charge all sizes of batteries
- Automatic charging current selection
- Two charging channels, can charge 2 or 4 pcs NiMH AA, AAA, C or D
- Additional charging slots for 1 or 2 pcs NiMH 9V batteries
- 3 LED indicators

PB09

SPECIALTY
PowerBank

- Special design for charging 9V batteries
- Charge 1 or 2 pcs NiMH 9V
- Two LED indicators

2 x 170mAh 9V

Premium Series Fast Series

	PowerBank V800C	PowerBank V600D	PowerBank H650C	PowerBank H500	PowerBank Express	PowerBank U-Smart	PowerBank Smart-2
Model Number	GPPB80	GPPB60	GPPB65	GPPB50	GPPB15	GPPB13	GPPB14
Charging Time	~15 mins	~1-2 Hours	~1 Hour	~2-4 Hours	~15 mins	~30 mins	~1 Hour
Charging Channel	4 Channels	4 Channels	4 Channels	4 Channels	4 Channels	4 Channels	4 Channels
Configuration	Corded Type	Corded Type	Corded Type	Corded Type	Corded Type	Corded Type	Corded Type
Input Voltage	100-240V AC 50/60Hz 12V DC	100-240V AC 50/60Hz 12V DC	100-240V AC 50/60Hz 12V DC	100-240V AC 50/60Hz (EU/UK) 100-120V AC 60Hz (US)	100-240V AC 50/60Hz 14V DC	100-240V AC 50/60Hz 12V DC	100-240V AC 50/60Hz 12V DC
Output Voltage	DC 12V 3.3A	DC 12V 1A	DC 12V 1.5A	DC 1.6V	DC 14V 4.5A	DC 12V 2.5A	DC 12V 1.5A
Battery Type	NiMH	NiMH	NiMH	NiMH	NiMH	NiMH	NiMH
Battery Size	4 x AA/AAA	4 x AA/AAA	4 x AA/AAA	4 x AA/AAA	4 x AA/AAA	4 x AA/AAA	4 x AA/AAA
Car Charging Function	✓	✓	✓	✓	✓	✓	✓
Charging Current							
-AA	1-2 pcs – 7000mA 3-4 pcs – 4000mA	1-2 pcs – 2200mA 3-4 pcs – 1100mA	2000mA	1-2 pcs - 1150mA 3 pcs - 766mA 4 pcs - 575mA	7000mA	3400mA	NiMH-2000mA
-AAA	3400mA	1100mA	1000mA	1-2 pcs - 475mA 3 pcs - 317mA 4 pcs - 237.5mA	3400mA	1700mA	NiMH-1000mA
Trickle Charge	✓	✓	✓	✓	✓	✓	✓
Termination Method							
-Minus Delta Voltage (-dV)	Individual	Individual	Individual	Individual	Individual	Individual	Individual
-Safety Timer	Individual	Individual	Individual	Individual	Individual	Individual	Individual
-Temperature Protection	Individual	Individual	Individual	Individual	Individual	Individual	Individual
-Alkaline Battery Detection	✓	✓	✓	✓	✓	✓	✓
-Damaged Battery Detection	✓	✓	✓	✓	✓	✓	✓
LED Indicator	3-Color Icons x 7	3-Color Icons x 7	3-Color Icons x 7	3-Color Icons x 7	Red x 1	Dual color x 4	Orange x 4
Safety Approval or Compliance	CE/GS/UL/ FCC	CE/GS/UL/ FCC/Energy Star	CE/GS/UL/ FCC/Energy Star	CE/GS/UL/PSE FCC/Energy Star	CE/GS/UL/ FCC	CE/GS/UL/FCC/ SAA	CE/GS/UL/FCC/ SAA/Energy Star
Dimension (L)x(W)x(T) mm	126 x 38 x 89.5	126 x 38 x 89.5	125 x 75 x 29	116 x 72.5 x 32	135 x 80 x 41	120 x 74 x 47	115 x 80 x 31.5

Mid-Range Series

	PowerBank M520	PowerBank M530	PowerBank M540	Mini PowerBank Quick
Model Number	GPPB520	GPPB530	GPPB540	GPPB25
Charging Time	~2-5 Hours	~2 Hours	~3 Hours	~5 Hours
Charging Channel	2 Channels	2 Channels	4 Channels	2 Channels
Configuration	Corded Type	Plug-in Type Foldable USB Plug	Plug-in Type Foldable US plug Detachable UK & EU plugs	Plug-in Type Foldable US Plug
Input Voltage	100-240V AC 50/60Hz	5V DC	100-240V AC 50/60Hz	100-240V AC 50/60Hz
Output Voltage	DC 3.2V 1050mA	DC 1.4V	DC 1.4V	DC 1.4V
Battery Type	NiMH	NiMH	NiMH	NiMH
Battery Size	4 x AA 2 x AAA	2 x AA/AAA/AAAA	4 x AA/AAA	2 x AA/AAA
Car Charging Function	✓	--	--	--
Charging Current				
-AA	2 pcs - 1050mA 4 pcs - 525mA	1pc - 850mA 2 pcs - 425mA	600mA	500mA
-AAA	2 pcs - 525mA	1 pc - 850mA 2 pcs - 425mA	600mA	220mA
-AAAA	--	1 pc - 850mA 2 pcs - 425mA	--	--
Trickle Charge	✓	✓	✓	✓
Termination Method				
-Minus Delta Voltage (-dV)	✓	Individual	Individual	--
-Safety Timer	✓	Individual	✓	✓
-Temperature Protection	✓	✓	Individual	✓
-Alkaline Battery Detection	✓	✓	✓	✓
-Damaged Battery Detection	✓	✓	✓	✓
LED Indicator	Dual color x 1	Dual color x 1	Dual color x 1	Dual color x 1
Safety Approval or Compliance	CE/GS/UL/FCC	CE/FCC	CE/GS/UL/FCC	CE/GS/ETL/FCC/Energy Star
Dimension (L)x(W)x(T) mm	108 x 66 x 29	40 x 80 x 22.5	75.1 x 64 x 37.3	107 x 48 x 36

Mid-Range Series

Standard Series

	PowerBank Quick 3	PowerBank Mega	PowerBank Nite-Lite	PowerBank	Mini PowerBank
Model Number	GPPB27	GPPB22	GPPB11	GPKB01	GPKB02
Charging Time	~8 Hours	~6 Hours	~10 Hours	~10 Hours	~10 Hours
Charging Channel	2 Channels	2 Channels	2 Channels	2 Channels	2 Channels
Configuration	Plug-in Type Foldable US plug	Corded Type	Plug-in Type Foldable US plug	Plug-in Type Foldable US plug	Plug-in Type Foldable US plug
Input Voltage	100-240V AC 50/60Hz	230V AC 50Hz (EU) 240V AC 50Hz (UK) 120V AC 60Hz (US)	230V AC 50Hz (EU/UK) 120V AC 60Hz (US)	230V AC 50Hz (EU/UK) 120V AC 60Hz (US)	230V AC 50Hz (EU/UK) 120V AC 60Hz (US)
Output Voltage	DC 2.8V (AA/AAA) DC 5V 500mA (USB output)	DC 5.6V	DC 2.8V (AA/AAA) DC 9V (9V)	DC 2.8V	DC 1.4V
Battery Type	NiMH	NiMH	NiMH	NiMH	NiMH
Battery Size	4 x AA 2 x AAA	8 x AA/AAA	4 x AA/AAA 2 x 9V	4 x AA/AAA	2 x AA/AAA
Charging Current					
-AA	360mA	500mA	220mA	220mA	220mA
-AAA	160mA	200mA	85mA	100mA	100mA
-9V	--	--	24mA	--	--
Trickle Charge	✓	✓	--	--	--
Termination Method					
-Minus Delta Voltage (-dV)	--	--	--	--	--
-Safety Timer	✓	✓	--	--	--
-Temperature Protection	✓	✓	--	--	--
-Alkaline Battery Detection	✓	--	--	--	--
-Damaged Battery Detection	✓	--	--	--	--
LED Indicator	Dual color x 1	Dual color x 2	Green x 2	Green x 2	Green x 2
Safety Approval or Compliance	CE/GS/ETL/FCC/Energy Star	CE/GS/UL/FCC	CE/GS/UL/FCC	CE/GS/UL/SAA/FCC	CE/GS/UL/FCC
Dimension (L)x(W)x(T) mm	119 x 79.8 x 32	116 x 90 x 31	110.5 x 73 x 45	106 x 66 x 32	104 x 43 x 28

Standard Series

Specialty Series

	PowerBank S350	PowerBank S360	PowerBank Universal	PowerBank Specialty
Model Number	GPPB350	GPPB360	GPPB19	GPPB09
Charging Time	~11 Hours	~11 Hours	D: 2200mAh~5 Hours; 7000mAh~16 Hours C: 2200mAh~5 Hours; 3500mAh~10 Hours AA: 1300mAh~5 Hours; 2000mAh~10 Hours AAA: 600mAh~5 Hours; 800mAh~9 Hours 9V: 170mAh~16 Hours	~10 Hours
Charging Channel	2 Channels	2 Channels	2 Channels	2 Channels
Configuration	Plug-in Type	Plug-in Type	Corded Type	Plug-in Type
Input Voltage	230V AC 50Hz (EU/UK) 120V AC 60Hz (US)	230V AC 50Hz (EU/UK) 120V AC 60Hz (US)	230V AC 50Hz (EU) 240V AC 50Hz (UK) 120V AC 60Hz (US)	230V AC 50Hz (EU/UK) 120V AC 60Hz (US)
Output Voltage	DC 2.8V	DC 1.4V	D/C/AA/AAA: DC 2.8V 9V: DC 9V	DC 9.8V
Battery Type	NiMH	NiMH	NiMH	NiMH
Battery Size	4 x AA/AAA	2 x AA/AAA	4 x D/C/AA/AAA 2 x 9V	2 x 9V
Charging Current				
- D	--	--	560mA	--
- C	--	--	440mA	--
- AA	200mA	200mA	260mA	--
- AAA	100mA	100mA	120mA	--
- 9V	--	--	14mA	24mA
Trickle Charge	--	--	--	--
Termination Method				
-Minus Delta Voltage (-dV)	--	--	--	--
-Safety Timer	--	--	--	--
-Temperature Protection	--	--	--	--
-Alkaline Battery Detection	--	--	--	--
-Damaged Battery Detection	--	--	--	--
LED Indicator	Red x 2	Red x 2	2 Green for 2 Channels; 1 Green for 9V	Green x 2
Safety Approval or Compliance	CE/GS/UL/FCC	CE/GS/UL/PSE/FCC	CE/GS/UL/FCC	CE/GS/UL/FCC
Dimension (L)x(W)x(T) mm	105 x 44 x 46	105 x 44 x 34.5	178 x 97 x 57	98.6 x 66.2 x 60

AA

270AAHC-U2 1.2V

250AAHC-U2 1.2V

230AAHC-U2 1.2V

210AAHC-U2 1.2V

270AAHC-U4 1.2V

250AAHC-U4 1.2V

230AAHC-U4 1.2V

210AAHC-U4 1.2V

180AAHC-U2 1.2V

160AAHC-U2 1.2V

130AAHC-U2 1.2V

180AAHC-U4 1.2V

160AAHC-U4 1.2V

130AAHC-U4 1.2V

AAA

100AAAHC-U2 1.2V



85AAAHC-U2 1.2V

80AAAHC-U2 1.2V

100AAAHC-U4 1.2V

85AAAHC-U4 1.2V

80AAAHC-U4 1.2V

75AAAHC-U2 1.2V

70AAAHC-U2 1.2V

65AAAHC-U2 1.2V

60AAAHC-U2 1.2V

75AAAHC-U4 1.2V

70AAAHC-U4 1.2V

65AAAHC-U4 1.2V

60AAAHC-U4 1.2V

C

350CHC-U2 1.2V

220CH-U2 1.2V

D

900DHC-U2 1.2V

700DHC-U2 1.2V

450DHC-U2 1.2V

220DH-U2 1.2V

9V

17R8H-U1 8.4V

NiMH RECHARGEABLE BATTERIES

Cell Size	Model No.	Nominal Voltage (V)	Capacity (0.2C discharge)*(mAh) Minimum	Typical	Nominal Dimension (mm) Diameter	Height	Weight (g)	Standard Charge Current (mA)	Time (Hour)	1 Hr Charge Current (mA)#
NICKEL METAL HYDRIDE SERIES										
AA	270AAHC	1.2	2500	2600	14.5	50.5	31.5	250	16	2500
	250AAHC	1.2	2400	2450	14.5	50.5	31	240	16	2400
	230AAHC	1.2	2200	2250	14.5	50.5	29.5	220	16	2200
	210AAHC	1.2	2000	2050	14.5	50.5	28	200	16	2000
	180AAHC	1.2	1750	1800	14.5	50.5	26	180	16	1800
	160AAHC	1.2	1550	1600	14.5	50.5	26	160	16	1600
	130AAHC	1.2	1250	1300	14.5	50.5	26	130	16	1300
AAA	100AAAHC	1.2	930	970	10.5	44.5	15.2	93	16	930
	85AAAHC	1.2	830	850	10.5	44.5	14.2	85	16	850
	80AAAHC	1.2	780	800	10.5	44.5	14	80	16	800
	75AAAHC	1.2	730	750	10.5	44.5	13	75	16	750
	70AAAHC	1.2	680	700	10.5	44.5	12.2	70	16	700
	65AAAHC	1.2	630	650	10.5	44.5	13	65	16	650
	60AAAHC	1.2	600	630	10.5	44.5	13	60	16	600
C	350CHC	1.2	3480	3500	26.2	50	78.5	350	16	NA
	220CH	1.2	2150	2200	26.2	50	61	220	16	NA
D	900DHC	1.2	8750	9000	34.2	61.5	173	900	16	NA
	700DHC	1.2	6800	7000	34.2	61.5	155	700	16	NA
	450DHC	1.2	4400	4500	34.2	61.5	130	450	16	NA
	220DH	1.2	2150	2200	34.2	61.5	71	220	16	NA
9V	17R8H	8.4	170	175	15.7(T) x 26.5(W) x 48.5(H)		32	17	16	170

One hour rate with charge termination control. * After charging at 0.1 C for 16 hours.

Distributed by:

GP Batteries

WORLDWIDE HEADQUARTERS
Hong Kong
GPI International Limited

Gold Peak Building, 8/F., 30 Kwai Wing Road, Kwai Chung, N.T., Hong Kong
Tel : (852) 2484 3333 Fax : (852) 2480 5912
E-mail address : gpii@goldpeak.com Website : http://www.gpbatteries.com

SALES AND MARKETING BRANCH OFFICES

ASEAN
GP BATTERY MARKETING (SINGAPORE) PTE. LIMITED
97 Pioneer Road, Singapore 639579
Tel: (65) 6559 9760 Fax: (65) 6559 9761

MALAYSIA
GP BATTERY MARKETING (MALAYSIA) SDN. BHD.
Lot 8, Jalan Pemberita U1/49,
Temasya Industrial Park,
40150 Shah Alam, Selangor Darul Ehsan, Malaysia
Tel: (60) 3 5569 3499 Fax: (60) 3 5569 3498

THAILAND
GP BATTERY MARKETING (THAILAND) CO., LIMITED
102 Soi Sukhumvit 26, Sukhumvit Road,
Klongton, Klongtoey, Bangkok 10110 Thailand
Tel: (66) 2 661 3688 Fax: (66) 2 661 3602

TAIWAN
GOLD PEAK INDUSTRIES (TAIWAN) LIMITED - TAIPEI OFFICE
8/F, No.205, Sec. 1, Fu Xing South Road,
Taipei 10666, Taiwan R.O.C.
Tel: (886) 2 2772 9998 Fax: (886) 2 2731 4868/ 2741 0192

CHINA
HUIZHOU CHAO BA BATTERIES COMPANY LTD
No.29, 6th Gaoxin Road,
Zhongkai Gaoxin Industrial Zone,
Huizhou City, Guangdong, China
(Postal Code: 516006)
Tel: (86) 752 2638 698 Fax: (86) 752 2638 666

HONG KONG
GP BATTERY MARKETING (H.K.) LIMITED
Unit D & E, 1/F, Kam Bun Industrial Building,
No.13-19 Kwai Wing Road,
Kwai Chung, N.T., Hong Kong
Tel: (852) 2420 0281 Fax: (852) 2494 9349

KOREA
GP BATTERY MARKETING (KOREA) LIMITED
5/F, WhaDeok Bldg, 319-11, Yangjae-dong,
Seocho-gu, Seoul, South Korea
Tel: (822) 549-7188/9 Fax: (822) 514-0623

U.S.A.
GOLD PEAK INDUSTRIES (NORTH AMERICA) INC.
11235 West Bernardo Court, San Diego,
CA 92127-1638, U.S.A.
Tel: (1) 858 674 6099 Fax: (1) 858 674 6496/ 674 5883

CANADA
GP BATTERY MARKETING INC.
Unit 7, 7780 Woodbine Avenue, Markham,
Ontario, Canada L3R 2N7
Tel: (1) 905 474 9507 Fax: (1) 905 474 9452

LATIN AMERICA
GP BATTERY MARKETING (LATIN AMERICA) INC.
8370 NW, 66TH Street, Miami, Florida 33166, U.S.A.
Tel: (1) 305 471 7717 Fax: (1) 305 471 7718

EUROPE
GP BATTERIES EUROPE B.V.
Kortijzer 4, 5721 VE Asten,
Netherlands
Tel: (31) 493 681030 Fax: (31) 493 681039

FRANCE
GP BATTERIES MARKETING FRANCE - GPBMF
ZAE du Trou Grillon - BP49,
91280 Saint Pierre du Perray - France
Tel: (33) 1 6989 6200 Fax: (33) 1 6989 6210

GERMANY
GP BATTERY MARKETING (GERMANY) GMBH
Schiessstrasse 68, D-40549 Düsseldorf, Germany
Tel: 49 (0) 211 522 9540 Fax: 49 (0) 211 522 954 54

POLAND
GP BATTERY (POLAND) SP. ZO.O.
Al. Jerozolimskie 162, 02-342 Warsaw, Poland
Tel: (48) 22 500 9500 Fax: (48) 22 846 7535

U.K.
GP BATTERIES (U.K.) LIMITED
Monument View, Chelston Business Park,
Wellington, Somerset, TA21 9ND, United Kingdom
Tel: (44) 1 823 660 044 Fax: (44) 1 823 665 595

ITALY
GP BATTERY MARKETING ITALY S.R.L.
Via, Alessandro Volta 3,
20094 Assago (Mi), Italy
Tel: (39) 02 488 2512 Fax: (39) 02 488 2865

SCANDINAVIA
GPBM NORDIC AB
Grimboåsen 5, SE-417 49 Goteborg, Sweden
Tel: (46) 31 799 1600 Fax: (46) 31 799 1613

RUSSIA
AZ COMPANY
Building 4, 2-D Zaborje str.
Mic. Dist. Vostryakovo, Domodedovo
142072 Moscow Area, Russia
Tel: (7) 495 540 5050 Fax: (7) 495 926 5050 ext. 201

MIDDLE EAST
GP Middle East FZC
P.O.Box 7989, Suite No. L1-18,
Saif Zone, Sharjah, United Arab Emirates
Tel: (971) 6 5578787 Fax: (971) 6 5578777

GPPA8PB-A 09/09
All rights reserved. No parts of this catalogue written or pictorial may be reproduced without the permission of GPI International Ltd.